



11 Hours of Battery Life

(Micro-B USB type)



Float'n Flash



Optional Speaker-Microphone, HM-213



*For illustration purpose only

IC-M25EURO

FEATURES

Slim, Lightweight, **High Performance**

The IC-M25EURO has the slimmest (depth: 30.5mm) and lightest (220g) body as a floating marine transceiver*. It also delivers uncompromised performance that will exceed expectations.

*As of July, 2015, researched by Icom.

Large LCD, Simple User Interface

The IC-M25EURO's LCD is 30% larger than its predecessor, the IC-M23 and shows clearly large channel number and status icons. The buttons on the front panel are well laid out and provide simple and straightforward operation.

USB Charging (Micro-B USB type)

A standard USB connector (Micro-B type) is used for charging the IC-M25EURO. Cigarette lighter cables or mobile batteries for charging smartphones or other devices can be used with the IC-M25EURO*.

* The IC-M25EURO accepts 5V/1A (Max.) input. Use of third-party products is not guaranteed.

Float'n Flash

The IC-M25EURO floats and lets you know where it is with the flashing red LED light and LCD/key backlight.

11 Hours of Battery Life

The built-in 1500mAh lithium-ion battery allows 11 hours (approx.) of long operation*.

* Typical operation with Tx (Hi): Rx: standby=5:5:90

Optional Speaker-Microphone, HM-213

The optional waterproof speaker-microphone, HM-213, provides commercial grade convenience while mounting the radio around the waist. The radio floats even when the HM-213 is attached.

550mW Audio Output

The IC-M25EURO provides a powerful 550mW (typical) audio output and received voice can be heard loud and clear.

Other Features

- IPX7 waterproof construction (1m depth of water for 30 minutes)
- · 4-step battery life indicator
- Dual/Tri-watch functions*
- Instant access to Ch 16 or programmable call channel
- Favorite channel function
- · Monitor function opens noise squelch
- Auto scan function*
- LCD auto backlighting
- AquaQuake[™] draining function
- * Not available in the HOL version

SPECIFICATIONS

GENERAL		
Frequency range Tx Rx	156.000–161.450MHz 156.000–163.425MHz	
Usable channel groups	INT, USA*, ATIS* channels * Depending on version	
Type of emission	16K0G3E (FM)	
Power supply voltage	3.7V DC nominal	
Current drain (at 3.7V DC) Tx Rx (Internal SP/External SP) Operating temperature range	2.3A 300mA/200mA (Max. audio) 15°C to +55°C	
Antenna impedance	50Ω	
Dimensions (W×H×D) (projections not included)	56.6×134.2×30.5mm	
Weight (approximately)	220g (With FA-SC59V and MB-133)	
TRANSMITTER		
Output power	5W (approx.)/1W/0.5W* * For only FRG version	
Max. frequency deviation	±5.0kHz	
Frequency stability	±1.5kHz	
Spurious emissions	0.25µW	
Adjacent channel power	70dB	
Residual modulation	40dB	

Measurements made in accordance with EN301-178. All stated specifications are subject to change without notice or obligation

70dB

68dB

External SP 200mW (4Ω load)

Internal SP 550mW typ. (12Ω load, at 1 kHz)

-6dBµ emf typ. (at 20dB SINAD)

-6dBμ emf typ. (at threshold)

Applicable IP Rating

RECEIVER

Squelch sensitivity

Spurious response

Audio output power (at 10% distortion)

Intermodulation

Adjacent channel selectivity

Sensitivity

Ingress Protection Standard	
Water	IPX7 (Waterproof protection)

OPTIONS Some options may not be available in some countries. Please ask your dealer for details.













The "3D GENUINE Icom label" is attached to the rear panel.

Check the Icom website for details: http://www.icom.co.jp/world/genuine-info/

lcom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other products or brands are registered trademarks or trademarks of their respective holders.

ICOM Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.

12421 Willows Road NE, Kirkland, WA 98034, U.S.A. Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com URL: http://www.icomamerica.com

Icom Canada

Glenwood Centre #150-6165 Highway 17A, Delta, B.C., V4K 5B8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-0 Fax: +49 (6196) 76685-50 mail: info@icomeurope.com URL: http://www.icomeurope.com

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" Bajos A 08174, Sant Cugat del Valles, Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46 mail: icom@icomspain.com URL: http://www.icomspain.com

Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 GGZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00 :-mail: icom@icom-france.com URL: http://www.icom-france.com

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road, Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505 E-mail: sales@icom.net.au URL: http://www.icom.net.au

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C. Phone: +886 (02) 2559 1899 Fax: +886 (02) 2559 1874 E-mail: sales@asia-icom.com URL: http://www.asia-icom.com

Your local distributor/dealer: